

# DUBHE

**EunSung O&C Co.,Ltd**

576-5 Shinsadong Kangmangu

Seoul, Korea


**General**

Class	ABS +A1, MODU
Type	Offshore Self Elevating Unit Hydraulic pin type Temporary unrestricted navigation
Yard	South Korea
Built	2016
Flag / Port of Registry	BELZE/BELIZE

**Crane Specification**

Maker	LIEBHERR BOS 14000-500D GERMANY
Type	Offshore Pedestal Crane
Capacity	500 tons @ 20m radius
Max. Boom Length	60.00m, 72.00 m

**Helideck**

19.5 m(D-Value) / 9.3 tons(MTOM) / Suitable for Super Puma AS332L2

**Operating Survival Condition**

<Parameter>	<Operating Condition>	<Survival Condition>
Max. Water Depth	50.00 m	40.00 m
Wave Height	1.50 m	8.00 m
Wind Speed(1 min sustained)	25.80 m/s	51.50 m/s
Surface Current	2.00 m/s	2.00 m/s

**Main dimensions**

Length	63.00 m
Breadth	38.00 m
Depth	6.00 m
Payload	3,000 tons
Draft max	4.20 m
Accommodation	Min. 74 people
Leg Length	Min 78.6m + 13m(Extension)
Leg Diameter	3.50 m
Spudcan	Dia. 5.50 m
Jacking System	Bosch Rexroth
Jacking Speed	max. 36.00 m/h
Winches	4 x 30 tons Line Pull
Anchors	Delta Flipper 4 x 6 tons
Free Deck Space	1,520 m <sup>2</sup> (40 m x 38 m)
Moonpool	1 ea(Dia. 900mm)